



Dry



Wet



Heat



Oily



Cold



Chemical



TG1040

A comfortable seamless knitted glove with X-Dura Nitrile Foam palm dip for use in multiple environments and general handling. Good abrasion and tear resistance.

Key Features

- Suitable for dry, wet and oily conditions, maintaining grip
- A good choice for general handling, low risk tasks

Ideal for

- Automotive
- Construction and Utility
- Engineering and Manufacturing
- Warehousing and Logistics
- Waste, Recycling and Local Authority

Sizes:	6-11	Gauge:	15gg
Liner:	Nylon	Coating:	LiquiDex
No/Bag:	10	No/Carton:	100

TG1040

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
15 gauge

Liner Type
Nylon

Glove colour
Pantone 1795c / R:223 G:59 B:48 / C:8 M:96 Y:100 K:1

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
Flat Nitrile

Dip Application
Knuckle Dipped

Glove Treatment
LiquiDex



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
300mm x 450mm x 300mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.