

EN 511:2006



X 1 X



Dry



Wet



Heat



Oily



Cold



Chemical



EN 388:2016

4 X 4 3 D



TG5070

A flexible, comfortable single layer winter ready glove with X-Dura Latex matt finish palm coating for excellent grip in wet and dry conditions. Brushed acrylic inner lining and level D cut protection.

Key Features

- A single layer thermal glove that delivers dexterity and high levels of wearer comfort
- Brushed acrylic liner to keep hands warm whatever the weather
- X-Dura latex palm coating for optimum grip

Ideal for

- Scaffolding and outdoor construction trades
- Rail industry
- Cold stores

Sizes:	6-11	Gauge:	7gg
Liner:	Acrylic/PPE/Glass	Coating:	X-Dura Latex
No/Bag:	10	No/Carton:	100

TG5070

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
7 gauge

Liner Type
Acrylic/HPPE/Glass fibre

Glove colour
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
X-Dura Matt Latex

Dip Application
Palm Dipped

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
300mm x 450mm x 300mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.