



Dry



Wet



Heat



Oily



Cold



Chemical



TG5340

A comfortable superfine Cut Level D liner with an X-Dura Nitrile Foam palm dipped coating. Excellent grip and a full length cuff for use in wet, dry and oily conditions with touchscreen compatibility.

Key Features

- Superfine gauge close fitting and breathable liner
- Impressive comfort and dexterity
- Highly durable and tear resistant
- Nitrile foam coating makes it suitable for use in dry, wet and oily conditions
- Features a thumb crotch for extra protection and wear life

Ideal for

- Automotive
- Construction and Utility
- Engineering and Manufacturing
- Food Manufacturing and Prep
- Warehousing and Logistics
- Rail
- Waste, Recycling and Local Authority

Sizes:	6-12	Gauge:	18gg
Liner:	Polyester, Polyamide, HPPE, Steel, Elastane	Coating:	X-Dura Nitrile
No/Bag:	10	No/Carton:	100



TG5340

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
18 gauge

Liner Type
Polyester/Polyamide/HPPE/Steel/Elastane

Glove colour
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
X-Dura Nitrile Foam

Dip Application
Palm Dipped

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
300mm x 450mm x 300mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.